# SAFETY DATA SHEET



1. Identification	
Product number	1000028615
Product identifier	SW051R Sprayway F
Company information	SPRAYWAY INC. 1000 Integram Dr


Company phone Emergency telephone US Emergency telephone outside US Version # Recommended use Recommended restrictions

1000028615 **SW051R Sprayway Retail - Glass Cleaner - 19oz Trigger (6ct) 1000028615** SPRAYWAY INC. 1000 Integram Dr Pacific, MO 63069 United States 1-630-628-3000 1-866-836-8855 1-952-852-4646 01 Cleaner

# 2. Hazard(s) identification

Physical hazards
Health hazards
OSHA defined hazards

#### Label elements



Flammable aerosols

None known.

Category 1



	•
Signal word	Danger
Hazard statement	Extremely flammable aerosol.
Precautionary statement	
	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	Wash hands after handling.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

# 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	2.5 - 10
Ethyl Alcohol		64-17-5	2.5 - 10
Nitrogen		7727-37-9	0.01 - 0.1
Other components below	w reportable levels		90 - 100

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

# 4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.

Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Not available.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
	Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.
6. Accidental release meas	ures
protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 1 Aerosol.
	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

#### **Occupational exposure limits**

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3
		50 ppm
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

	Туре	e	Va	llue
			10	00 ppm
US. ACGIH Threshold Lir				
Components	Турс	e	Va	llue
2-Butoxyethanol (CAS 111-76-2)	TWA			ppm
Ethyl Alcohol (CAS 64-17-	5) STE	L	10	00 ppm
US. NIOSH: Pocket Guide Components	e to Chemical Hazards Type		Va	lue
2-Butoxyethanol (CAS 111-76-2)	TWA	Ą	24	mg/m3
Ethyl Alcohol (CAS 64-17-	5) TWA	Ą	19	opm 00 mg/m3 00 ppm
ological limit values				
ACGIH Biological Expose Components	ure Indices Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
* - For sampling details, pl	ease see the source do	cument.		
posure guidelines				
US - California OELs: Sk	in designation			
	5			
2-Butoxyethanol (CAS US - Minnesota Haz Subs	S 111-76-2)		e absorbed throu	ugh the skin.
2-Butoxyethanol (CAS	8 111-76-2) <b>s: Skin designation ap</b>   8 111-76-2)	plies	e absorbed throu esignation applie	-
2-Butoxyethanol (CAS US - Minnesota Haz Subs 2-Butoxyethanol (CAS	S 111-76-2) s: Skin designation ap S 111-76-2) kin designation S 111-76-2)	<b>plies</b> Skin d Can be		es.
2-Butoxyethanol (CAS US - Minnesota Haz Subs 2-Butoxyethanol (CAS US - Tennessee OELs: S 2-Butoxyethanol (CAS	5 111-76-2) <b>s: Skin designation ap</b> 5 111-76-2) <b>kin designation</b> 5 111-76-2) <b>to Chemical Hazards:</b> 5 111-76-2)	plies Skin d Can bo Skin designation Can bo	esignation applic e absorbed throu e absorbed throu	es. ugh the skin.
2-Butoxyethanol (CAS US - Minnesota Haz Subs 2-Butoxyethanol (CAS US - Tennessee OELs: S 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS	5 111-76-2) s: Skin designation app 5 111-76-2) kin designation 5 111-76-2) to Chemical Hazards: 5 111-76-2) its for Air Contaminant 5 111-76-2)	plies Skin d Can be Skin designation Can be ts (29 CFR 1910.10 Can be	esignation applie e absorbed throu e absorbed throu <b>100)</b> e absorbed throu	es. ugh the skin. ugh the skin. ugh the skin.
2-Butoxyethanol (CAS US - Minnesota Haz Subs 2-Butoxyethanol (CAS US - Tennessee OELs: S 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limit	5 111-76-2) <b>s: Skin designation ap</b> 5 111-76-2) <b>kin designation</b> 5 111-76-2) <b>to Chemical Hazards:</b> 5 111-76-2) <b>its for Air Contaminant</b> 5 111-76-2) Good general vent should be matched or other engineerin	plies Skin d Can be Skin designation Can be ts (29 CFR 1910.10 Can be ilation (typically 10 d to conditions. If ap ng controls to mainte	esignation applie e absorbed throu e absorbed throu 000) e absorbed throu air changes per oplicable, use pro ain airborne leve	es. ugh the skin. ugh the skin.
2-Butoxyethanol (CAS US - Minnesota Haz Subs 2-Butoxyethanol (CAS US - Tennessee OELs: S 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limi 2-Butoxyethanol (CAS propriate engineering	<ul> <li>S 111-76-2)</li> <li>s: Skin designation apples</li> <li>S 111-76-2)</li> <li>kin designation</li> <li>S 111-76-2)</li> <li>to Chemical Hazards:</li> <li>S 111-76-2)</li> <li>its for Air Contaminant</li> <li>S 111-76-2)</li> <li>Good general vent should be matched or other engineerin exposure limits have</li> <li>res, such as personal parts</li> </ul>	plies Skin d Can be Skin designation Can be is (29 CFR 1910.10 Can be ilation (typically 10 d to conditions. If ap ng controls to mainta ve not been establis	esignation applie e absorbed throu e absorbed throu oo) e absorbed throu air changes per oplicable, use pro ain airborne leve shed, maintain a ent	es. ugh the skin. ugh the skin. ugh the skin. hour) should be used. Ventilation rates pocess enclosures, local exhaust ventilati ils below recommended exposure limits.
2-Butoxyethanol (CAS US - Minnesota Haz Subs 2-Butoxyethanol (CAS US - Tennessee OELs: S 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limi 2-Butoxyethanol (CAS propriate engineering htrols	<ul> <li>S 111-76-2)</li> <li>s: Skin designation apples</li> <li>S 111-76-2)</li> <li>kin designation</li> <li>S 111-76-2)</li> <li>to Chemical Hazards:</li> <li>S 111-76-2)</li> <li>its for Air Contaminant</li> <li>S 111-76-2)</li> <li>Good general vent should be matched or other engineerin exposure limits have</li> <li>res, such as personal parts</li> </ul>	plies Skin d Can be Skin designation Can be ts (29 CFR 1910.10 Can be ilation (typically 10 d to conditions. If ap ng controls to mainta ve not been establis protective equipme	esignation applie e absorbed throu e absorbed throu oo) e absorbed throu air changes per oplicable, use pro ain airborne leve shed, maintain a ent	es. ugh the skin. ugh the skin. ugh the skin. hour) should be used. Ventilation rates pocess enclosures, local exhaust ventilati ils below recommended exposure limits.
2-Butoxyethanol (CAS US - Minnesota Haz Subs 2-Butoxyethanol (CAS US - Tennessee OELs: S 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limi 2-Butoxyethanol (CAS propriate engineering ntrols	<ul> <li>S 111-76-2)</li> <li>s: Skin designation apples</li> <li>S 111-76-2)</li> <li>kin designation</li> <li>S 111-76-2)</li> <li>to Chemical Hazards:</li> <li>S 111-76-2)</li> <li>its for Air Contaminant</li> <li>S 111-76-2)</li> <li>Good general vent should be matched or other engineerin exposure limits have</li> <li>res, such as personal personal</li></ul>	plies Skin d Can be Skin designation Can be ts (29 CFR 1910.10 Can be ilation (typically 10 d to conditions. If ap ng controls to maint we not been establis protective equipme es with side shields	esignation applie e absorbed throu e absorbed throu oo) e absorbed throu air changes per oplicable, use pro ain airborne leve shed, maintain a ent (or goggles).	es. ugh the skin. ugh the skin. hour) should be used. Ventilation rates ocess enclosures, local exhaust ventilati is below recommended exposure limits. irborne levels to an acceptable level.
2-Butoxyethanol (CAS US - Minnesota Haz Subs 2-Butoxyethanol (CAS US - Tennessee OELs: S 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limi 2-Butoxyethanol (CAS propriate engineering htrols	S 111-76-2) s: Skin designation app S 111-76-2) kin designation S 111-76-2) to Chemical Hazards: S 111-76-2) its for Air Contaminant S 111-76-2) Good general vent should be matched or other engineerin exposure limits have res, such as personal p Wear safety glasse Wear appropriate of	plies Skin d Can be Skin designation Can be ts (29 CFR 1910.10 Can be ilation (typically 10 d to conditions. If ap ng controls to mainta ve not been establis protective equipme es with side shields chemical resistant g	esignation applie e absorbed throu e absorbed throu oo) e absorbed throu air changes per oplicable, use pro ain airborne leve shed, maintain a ent (or goggles).	es. ugh the skin. ugh the skin. ugh the skin. hour) should be used. Ventilation rates pocess enclosures, local exhaust ventilati ils below recommended exposure limits.
2-Butoxyethanol (CAS US - Minnesota Haz Subs 2-Butoxyethanol (CAS US - Tennessee OELs: S 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limi 2-Butoxyethanol (CAS propriate engineering ntrols	<ul> <li>S 111-76-2)</li> <li>s: Skin designation apples</li> <li>S 111-76-2)</li> <li>kin designation</li> <li>S 111-76-2)</li> <li>to Chemical Hazards:</li> <li>S 111-76-2)</li> <li>its for Air Contaminant</li> <li>S 111-76-2)</li> <li>Good general vent should be matched or other engineerin exposure limits have the should be matched or other engineering exposure limits have the should be appropriate of supplier.</li> <li>Wear suitable proteins</li> </ul>	plies Skin d Can be Skin designation Can be ts (29 CFR 1910.10 Can be ilation (typically 10 d to conditions. If ap to conditions. If ap	esignation applie e absorbed throu e absorbed throu oo) e absorbed throu air changes per oplicable, use pro ain airborne leve shed, maintain a ent (or goggles).	es. ugh the skin. ugh the skin. hour) should be used. Ventilation rates ocess enclosures, local exhaust ventilati is below recommended exposure limits. irborne levels to an acceptable level.
2-Butoxyethanol (CAS US - Minnesota Haz Subs 2-Butoxyethanol (CAS US - Tennessee OELs: S 2-Butoxyethanol (CAS US NIOSH Pocket Guide 2-Butoxyethanol (CAS US. OSHA Table Z-1 Limi 2-Butoxyethanol (CAS propriate engineering ntrols	<ul> <li>S 111-76-2)</li> <li>s: Skin designation apples</li> <li>S 111-76-2)</li> <li>kin designation</li> <li>S 111-76-2)</li> <li>to Chemical Hazards:</li> <li>S 111-76-2)</li> <li>its for Air Contaminant</li> <li>S 111-76-2)</li> <li>Good general vent should be matched or other engineerin exposure limits have the should be matched or other engineerin exposure limits have the should be matched or other engineerin exposure limits have the should be matched or other engineerin exposure limits have the should be matched or other engineerin exposure limits have the should be matched or other engineerin exposure limits have the should be matched or other engineerin exposure limits have the should be should be</li></ul>	plies Skin d Can be Skin designation Can be ts (29 CFR 1910.10 Can be ilation (typically 10 d to conditions. If ap to conditions. If ap	esignation applie e absorbed throu e absorbed throu out air changes per oplicable, use pro ain airborne leve shed, maintain a ent (or goggles). gloves. Suitable g	es. ugh the skin. ugh the skin. hour) should be used. Ventilation rates bcess enclosures, local exhaust ventilati ls below recommended exposure limits. irborne levels to an acceptable level. gloves can be recommended by the glov hical filter / organic vapor cartridge or an

Ap	peara	ance
	pour	11100

Physical state

Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	167.6 °F (75.3 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	98 - 118 psig @20C estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Heat of combustion (NFPA 30B)	1.87 kJ/g estimated
Oxidizing properties	Not oxidizing.
Specific gravity	0.984 estimated
10. Stability and reactivity	

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

# Symptoms related to the physical, chemical and toxicological characteristics

#### Information on toxicological effects

# Acute toxicity

Acute toxicity			
Components	Species	Test Results	
2-Butoxyethanol (CAS 111-76-	2)		
Acute			
Dermal			
LD50	Guinea pig	7.3 ml/kg, 4 Days	
		0.23 ml/kg, 24 Hours	
	Rabbit	435 mg/kg, 24 Hours	
		0.68 ml/kg, 24 Hours	
		0.63 ml/kg	
	Rat	> 2000 mg/kg, 24 Hours	
Inhalation			
LC50	Rabbit	400 ppm, 7 Hours	
	Rat	450 ppm, 4 Hours	
Oral	Debba		
LD100	Rabbit	695 mg/kg	
LD50	Dog	> 695 mg/kg	
	Guinea pig	1414 mg/kg	
	Mouse	1519 mg/kg	
	Rat	1746 mg/kg	
Ethyl Alcohol (CAS 64-17-5)			
<u>Acute</u>			
Inhalation LC50	Cat	85.41 mg/l, 4.5 Hours	
2000	Gui	43.68 mg/l, 6 Hours	
	Mouse	> 60000 ppm	
	Wouse	79.43 mg/l, 134 Minutes	
	Rat	> 115.9 mg/l, 4 Hours	
	nai		
Qual		51.3 mg/l, 6 Hours	
<b>Oral</b> LD50	Monkey	6000 mg/kg	
EDS0	Mouse	10500 ml/kg	
		> 5000 mg/kg	
	Pig		
	Rat	10470 mg/kg	
		7800 ml/kg	
* Estimates for product ma	ay be based on additional component d	ata not shown.	
Skin corrosion/irritation	Prolonged skin contact may cause		
Serious eye damage/eye irritation	Direct contact with eyes may caus	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitiza	tion		

Respiratory or skin sensitization	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall	Evaluation of Carcinogenicity		
2-Butoxyethanol (CAS 11	1-76-2) 3 Not classifiable as to carcinogenicity to humans.		
OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1050)		
Not regulated.			
US. National Toxicology Pro	ogram (NTP) Report on Carcinogens		
Not listed.			
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not likely, due to the form of the product.		
Chronic effects	May be harmful if absorbed through skin.		
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.		

# 12. Ecological information

Ecotoxicity		The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Components		Species Test Results		
2-Butoxyethanol (CAS 111-76-2)				
Aquatic				
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours	

Water flea (Daphnia magna)

Fathead minnow (Pimephales promelas) > 100.1 mg/l, 96 hours

7700 - 11200 mg/l, 48 hours

Fish

Aquatic	
Crustacea	

\* Estimates for product may be based on additional component data not shown.

EC50

LC50

Persistence and degradability No data is available on the degradability of this product.

#### Bioaccumulative potential

Partition coefficient n-o	ctanol / water (log Kow)	
2-Butoxyethanol	0.83	
Ethyl Alcohol	-0.31	
Nitrogen	0.67	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

#### 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

# 14. Transport information

#### DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

#### ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.



# 15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.		
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)			
Not regulated.			
CERCLA Hazardous Substa	nce List (40 CFR 302.4)		
Not listed. SARA 304 Emergency releas	a natification		
Not regulated.	se nouncation		
5	d Substances (29 CFR 1910.	1001-1050)	
Superfund Amendments and Re	authorization Act of 1986 (S	ARA)	
Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No	,	
SARA 302 Extremely hazard	ous substance		
Not listed.			
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting)			
Chemical name		CAS number	% by wt.
2-Butoxyethanol		111-76-2	2.5 - 10
Other federal regulations			
Clean Air Act (CAA) Section	112 Hazardous Air Pollutant	ts (HAPs) List	
Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)			
Not regulated.			
Safe Drinking Water Act (SDWA)	Not regulated.		
US state regulations			
US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.			

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-Butoxyethanol (CAS 111-76-2)

**US. Massachusetts RTK - Substance List** 

2-Butoxyethanol (CAS 111-76-2) Ethyl Alcohol (CAS 64-17-5) Nitrogen (CAS 7727-37-9)

#### US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2) Ethyl Alcohol (CAS 64-17-5) Nitrogen (CAS 7727-37-9)

#### US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2) Ethyl Alcohol (CAS 64-17-5) Nitrogen (CAS 7727-37-9)

### US. Rhode Island RTK

Not regulated.

#### US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date	06-22-2018
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names